H2O2 Gas Sterilizer GP 200 Technical Datasheet

Size of Chamber	
Cell Volume	200L
Cell Depth	860 mm
Cell Width	480 mm
Cell Height	420 mm
Drawers	2 pcs

Dimensions	Single Door		
Door Type	**Fully automatic vertical sliding door**		
External dimension		**200 L**	
Device Depth		1910 mm	-
Device Width		1000 mm	-
Device Height		2190 mm	-

Drawer size of 200 Lt.: 635x330x90mm (LxWxH)

GOLDBERG H2O2 Gas Sterilizer is designed and manufactured in compliance with the following requirements and standards:

Medical Device Directive	: 93/42/EEC as amended by directive 2007/47/EC
Device Classification	: Class IIb, acc. To EC MDD 93/42/EEC 2007/47/EC (Annex IX)
Low Voltage Directive	: 2006/95/EC - EN 60601-1-1
EMC Directive	: 2004/108/EC EN 60601-1-2
RF Power Generator	: 55011
Quality Management System Requirements	: EN - ISO 9001
Medical Devices – Quality management systems – Requirements for regulatory purposes	: ISO 13485
Environmental Management Systems – Requirements with guidance for use	: ISO 14001

Device	
Control System	PLC (Programmable Logic Controller)
Operation Mode	Fully Automatic / Button Command
Display Type	Color TFT, LCD Touch Screen
Display Sizes Available	7,0"
Key Pad	Touchscreen
Printer	32 Character/line, integrated thermal printer
Communication	RS232 Port
Warning System	Visual & Audio & Printed
Monitoring	Touchscreen
Mobility	Easy positioning on 4 castors (2 x swivel) and firm fixing on suspension legs.

Standard Programs
P1: FAST
P2: STANDARD
P3: INTENSIVE

Safety & Quality Features
√ Protects operator from electrical current leaks.
√ Emergency stop button.
√ Hepa filter for filtration.
√ Password protection.

Temperature
Range 50°C - 60°C (chamber)
Measurement (5 x PT 100 (DIN Class A) Sensors

Chamber	
Test Pressure	100 Millitorr
Test Temperature	50-60 °C
Working Temperature	55 °C
Working Pressure	760 Torr - 500 Millitorr

Construction
Body (Electrostatic powdered profile steel/AISI 304 stainless)
Chamber (Aluminium 5000 Series)
Door (Aluminium 5000 Series)
Panels Surrounding (Aluminium 5000 Series)
Chamber (Plated)

Installation Requirement	
Power	16 kW, 3 Phases / 380 VAC ±10

Optional Spare Parts
Cartridge for 200 Lt.: 6 Cycles/cartridge

Installation Conditions

At least 60 cm. space is needed on both lateral sides of the device to provide an effective technical service.

For more information, please contact:

ERYIGIT Medical Devices Inc.
IVOGSAN, 1453 Sok. No:3/1 Ostim
06370 Yenimahalle, ANKARA, TURKEY
Tel: +90 312 395 5795 (pbx); Fax: +90 312 395 57 96
www.eryigit.com.tr sales@eryigit.com.tr

This document is intended for the use of Distributors/Dealers/Customers of ERYIGIT MD Inc.
Reproduction in whole or in part by any other party is prohibited.
GP200©2015, ERYIGIT MD Inc. All rights reserved.
ERYIGIT specifications are given for reference only and are subject to change without any previous notice. Accessory/Product images are for illustrative purposes only .